




EUROROLL® ROLLER CONVEYORS

Commissioning Tracks for Crossways and Lengthways Transportation





Pallet lengthways transport with a combination of EUROROLL-Pallet Roller Tracks and Pallet Roller Conveyors up to max. 3 pallets.







Pallet lengthways transport

Pallet lengthways transport, depth of 2 pallets, with and without balance separator.



← moving direction


Pallet lengthways transportation, depth of 3 pallets, with and without balance separator.



VARIANTS

Short gravity roller conveyors for maximum 2 – 3 pallets can be realised cheaply with EUROROLL-Pallet Roller Tracks.

Whereas one can choose whether the pallet is conveyed in length or cross direction to their batten. This is the most effective solution for pallet cross transportation. The use of Brake Rollers is not necessary when there is a slight declination. Longer gravity roller conveyors are often more effective to be realised with single conveyors with continuous rollers.




Pallet crossways transport

Pallet crossways transport with maximum 3 pallets with EUROROLL-Pallet Roller Tracks (without brake rollers)

2 Roller Tracks (double-track) for pallets with a weight up to maximum 600 kg. Choosily with pallet separator for pressure-free unloading.

3 Roller Tracks (triple-track) for pallets with a weight up to maximum 1000 kg. Choosily with pallet separator for pressure-free unloading.



Across Batten Conveyors up to max. 4 Pallets

Conveyors for the across batten transport of pallets are equipped with 4 EUROROLL-Pallet Roller Tracks, Brake Rollers in sufficient quantity and a pallet separating device (alternatively with manual unlocking devise).

Delivery length: max. up to 8 m

