



FR Rouleau accumulatif avec double pignon en acier, équipé de 2 roulements à billes avec gorge. De par son système de couplage par frottement, ce rouleau convient pour le convoyage accumulatif avec contact. Pour produits mi-lourds avec base dure et plane.

D Stauangetriebene Tragrolle mit Stahl-Mehrfachkettenrad, ausgestattet mit zwei Rillenkugellagern. Durch Reibungs-kupplung ist diese Tragrolle geeignet für Akkumulations-Rollenbahn zum Transport von mittelschweren Produkten mit festem, flachem Boden. Auch lieferbar mit festem Kunststoff-Ring. Diese Ausführung nicht im Taktbetrieb einsetzen.

GB Accumulating conveyor roller with a double steel sprocket, fitted with two grooved ball bearings. Because it makes use of a friction coupling, this version is suitable for an accumulating roller conveyor for the transportation of lightweight products with hard and flat undersides. Also available with a fixed plastic ring exclusively for use in continuous transport.

SPECIFICATIONS:



1/2x5/16"
Z=13



0,05 - 0,07



STEEL C45



6202-6003



100 KG



ZINK PLATED - ORANGE

OPTIONS:



STEEL



SS

Spindel Steel/SS						
Ø 10	M 6 x 12		sw 8 x 10	Ø 10 x 10	M 10 x 15	met BD M 8 x 15
zk 11			sw 11 x 10			
Ø 12	M 6 x 12 M 8 x 15		sw 10 x 10	Ø 12 x 10	M 12 x 15	met BD M 10 x 15
Ø 14	M 8 x 15 M 10 x 15		sw 12 x 10	Ø 14 x 10	M 14 x 20	met BD M 10 x 15
Ø 15	M 8 x 15 M 10 x 15		sw 12 x 10	Ø 15 x 10		met BD M 14 x 20
Ø 17	M 10 x 15 M 12 x 20		sw 14 x 10 sw 12 x 10	Ø 17 x 12		met BD M 16 x 20

Tube	Steel Zinkplated	Stainless steel	PVC 5005	PVC 7011
Ø 50 x 1.5	x	x		
Ø 50 x 2.0	x	x		
Ø 50 x 2.8			x	x
Ø 60 x 1.5	x			
Ø 60 x 2.0	x	x		
Ø 63 x 3.0			x	x
Ø 63.5 x 2.9	x			
Ø 80 x 2.0	x	x		
Ø 82.5 x 3.2	x			
Ø 88.9 x 3.2	x	x		
Ø 90 x 7.0			x	x